



An ISO 9001:2015 Certified Co.

Product Data Sheet

DC Automatic Transmission Fluid DEX II-D

- SAE Crankcase Viscosity Grades: 10W
- Performance Standards: General Motor's automatic transmission fluid DEXRON II-D
- Usage Guidelines: superior quality transmission and power steering oil for modern automatic transmissions, ideal for transmission systems, power steering and hydraulic fluid applications
- Composition: Base Oil Group II, Additives: Automatic Transmission Fluid Additive Package (3 to 15%), Pour Point Depressant (0.4 to 2%), Red Colour (0.01 to 0.1%)

Physico-Chemical Properties: DC Automatic Transmission Fluid DEX II-D

S.No.	Characteristics	Test Method	SAE 10W
1	Kinematic Viscosity @100°C, cSt, min	IS 1448 P:25	4.1
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	180
3	Copper Strip Corrosion, 121°C, 1 hr	IS 1448 P:15	1
4	Max. Temp. for Viscosity of 60,000 cP, °C	ASTM D2983	-30

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.