



An ISO 9001:2015 Certified Co.

Product Data Sheet

DC Automatic Transmission Fluid TASA

- SAE Crankcase Viscosity Grades: 10W
- Performance Standards: General Motor's automatic transmission fluid Type 'A' Suffix 'A (TASA)
- Usage Guidelines: for light vehicles that have modern automatic transmission and power steering units
- Composition: Base Oil Group II, Additives: Automatic Transmission Fluid Additive Package (3 to 15%), Pour Point Depressant (0.4 to 2%), Red Colour (0.01 to 0.1%)

Physico-Chemical Properties: DC Automatic Transmission Fluid TASA

| S.No. | Characteristics | Test Method | SAE 10W |
|-------|--|--------------|---------|
| 1 | Kinematic Viscosity @100°C, cSt, min | IS 1448 P:25 | 4.1 |
| 2 | Flash Point, Cleveland (open) cup, °C, min | IS 1448 P:69 | 180 |
| 3 | Copper Strip Corrosion, 121°C, 1 hr | IS 1448 P:15 | 1 |
| 4 | Max. Temp. for Viscosity of 60,000 cP, °C | ASTM D2983 | -30 |

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.