



An ISO 9001:2015 Certified Co.

Product Data Sheet

DC Hydrofluorocarbons (HFCs) Immiscible Refrigerant Compressor Oil

- ISO Designation: ISO-L-DRE
- ISO Viscosity Grades: 15,22,32,46,68,100
- Performance Standards: ISO 6521-3: 2019, ISO 6743-3: 2003, IS 11159-4: 2011, IS 4578: 1997
- Usage Guidelines: Mobile air conditioning. Domestic refrigeration. Residential and commercial air conditioning and heat pump. Commercial refrigeration including transport refrigeration.
- Composition: Base Oil Group II, Additives: Specially Formulated Compressor Oil Additive Package (0.4 to 4%)

S.No	Characteristics	Test Method	15	22	32	46	68	100
1	Kinematic Viscosity @40°C, cSt, range		13.5 to 16.5	19.8 to 24.2	28.8 to 35.2	41.4 to 50.6	61.2 to 74.8	90 to 110
		IS 1448 P:25						
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	140	140	150	150	160	190
3	Pour Point, °C, max	IS 1448 P:10	-39	-36	-30	-24	-24	-24
4	ASTM Colour, max	IS 1448 P:12	0.5	0.5	0.5	0.5	0.5	1
5	Total Acidity, mg of KOH/g of oil, max	IS 1448 P:2	0.05	0.05	0.05	0.05	0.05	0.05
6	Inorganic Acidity, mg of KOH/g of oil	IS 1448 P:2	Nil	Nil	Nil	Nil	Nil	Nil
7	Ash Content, % by mass, Max	IS 1448 P:4	0.01	0.01	0.01	0.01	0.01	0.01
8	Copper Strip Corrosion, 100°C, 3 hrs	IS 1448 P:15	1	1	1	1	1	1
9	Water Content	IS 4578-A	passes crackle test					

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.