



An ISO 9001:2015 Certified Co.

Product Data Sheet

Cold Quenching Oil

- ISO Designation: ISO-L-UHD
- ISO Viscosity Grades: 10,32,68
- Performance Standards: ISO 6743-14:1994, IS 2664: 1980 Type C
- Usage Guidelines: Oils for fast hardening, for temperatures less than 130°C to harden uniformly with minimum cracking and distortions and constant predictable cooling rates
- Composition: Base Oil Group II, Additives: Quenching Oil Additive (1 to 10%)

Physico-Chemical Properties: Cold Quenching Oil

S.No.	Characteristics	Test Method	10	32	68
1	Kinematic Viscosity @40°C, cSt, range	IS 1448 P:25	11.5 to 17.5	20.5 to 36	36 to 73
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	160	175	200
3	Pour Point, °C, max	IS 1448 P:10	0	0	3
4	Acidity, organic mg of KOH/g of oil, max	IS 1448 P:2A	0.60	0.60	0.60
5	Inorganic Acidity, mg of KOH/g of oil	IS 1448 P:2C	Nil	Nil	Nil
6	Copper Strip Corrosion, 100°C, 3 hrs	IS 1448 P:15	1	1	1
8	Saponification Value	IS 1448 P:55	0.5	0.5	0.5

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.