



An ISO 9001:2015 Certified Co.

Product Data Sheet

DC Engine Oil CF-4

- SAE Crankcase Viscosity Grades: 15W40, 20W40
- Performance Standards: API CF-4, MB 228.1
- Usage Guidelines: for Off Highway Construction and Earth Moving Equipment, Heavy Duty Trucks, Buses, LCVs, SUVs, MUVs, Tractors, 3 Wheelers
- Composition: Base Oil Group II, Additives: Multipurpose Engine Oil Additive Package (3 to 10%), Red Colour (0.01 to 0.1 %) (only in SAE 20W-40), Pour Point Depressant (0.4 to 2%)

Physico-Chemical Properties: DC Engine Oil CF-4

S.No.	Characteristics	Test Method	SAE 15W40	SAE 20W40
1	Kinematic Viscosity @100°C, cSt, min	IS 1448 P:25	12.5	12.5
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	180	180
3	Copper Strip Corrosion, 121°C, 1 hr	IS 1448 P:15	1	1
4	Max. Temp. for Viscosity of 60,000 cP, °C	ASTM D2983	-25	-20

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.