



An ISO 9001:2015 Certified Co.

Product Data Sheet

DC Engine Oil CF

- SAE Crankcase Viscosity Grades: 30,40
- Performance Standards: API CF, Caterpillar Series 3, US-MIL-L2104C, Mack T-7 & T-8A test, IS 1356: 2014 EDL 3
- Usage Guidelines: for Off Highway Construction and Earth Moving Equipment, Heavy Duty Commercial Vehicles, LCVs, MUVs, Tractors, 3 Wheelers
- Composition: Base Oil Group II, Additives: Multipurpose Engine Oil Additive Package (3 to 10%), Red Colour (0.01 to 0.1 %)

Physico-Chemical Properties: DC Engine Oil CF

S.No.	Characteristics	Test Method	SAE 30	SAE 40
1	Kinematic Viscosity @100°C, cSt, min	IS 1448 P:25	9.3	12.5
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	180	180
3	Copper Strip Corrosion, 121°C, 1 hr	IS 1448 P:15	1	1

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.