



An ISO 9001:2015 Certified Co.

Product Data Sheet

DC Engine Oil CI-4

- SAE Crankcase Viscosity Grades: 15W40, 10W30
- Performance Standards: API CI-4, JASO DH1, KES 07.851
- Usage Guidelines: for Off Highway Construction and Earth Moving Equipment, Heavy Duty Trucks, Buses, LCVs, SUVs, MUVs, Tractors
- Composition: Base Oil Group II, Additives: Diesel Engine Oil Additive Package (10 to 25%), Pour Point Depressant (0.4 to 2%)

Physico-Chemical Properties: DC Engine Oil CI-4

S.No.	Characteristics	Test Method	SAE 15W40	SAE 10W30
1	Kinematic Viscosity @100°C, cSt, min	IS 1448 P:25	12.5	9.3
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	180	180
3	Copper Strip Corrosion, 121°C, 1 hr	IS 1448 P:15	1	1
4	Max. Temp. for Viscosity of 60,000 cP, °C	ASTM D2983	-25	-30

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.