



An ISO 9001:2015 Certified Co.

## Product Data Sheet

### DC Engine Oil CK-4

- SAE Crankcase Viscosity Grades: 15W40, 10W30
- Performance Standards: API CK-4, ACEA E9, MB 228.31, Volvo VDS 4.5, Cummins 20086, Caterpillar ECF 3, Mack EOS 4.5, Renault RLD 4
- Usage Guidelines: new generation Off Highway Construction and Earth Moving Equipment, Heavy Duty Trucks, Buses, LCVs, SUVs, MUVs, meet stringent lubrication requirements of the modern BS VI heavy duty diesel engines
- Composition: Base Oil Group II, Additives: Diesel Engine Oil Additive Package (10 to 25%), Pour Point Depressant (0.4 to 2%)

#### Physico-Chemical Properties: DC Engine Oil CK-4

S.No.	Characteristics	Test Method	SAE 15W40	SAE 10W30
1	Kinematic Viscosity @100°C, cSt, min	IS 1448 P:25	12.5	9.3
2	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	180	180
3	Copper Strip Corrosion, 121°C, 1 hr	IS 1448 P:15	1	1
4	Max. Temp. for Viscosity of 60,000 cP, °C	ASTM D2983	-25	-30

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.