



An ISO 9001:2015 Certified Co.

## Product Data Sheet

### DC Multigrade EP Gear Oil GL-4

- SAE Gear Viscosity Grades: 80W90, 85W140
- Performance Standards: IS 1118: 1992 EP Type GL-4, API GL-4, US MIL-L-2105
- Usage Guidelines: for both old and new generation vehicles including spiral, bevel, worm and synchromesh manual gears and transmission systems, improves efficiency of transmissions and axles under moderate to severe load and pressure conditions
- Composition: Base Oil Group II, Additives: Gear Oil Additive Package (0.4 to 4%)

Physico-Chemical Properties: DC Multigrade EP Gear Oil GL-4

S.No.	Characteristics	Test Method	SAE 80W90	SAE 85W140
1	Kinematic Viscosity @100°C, cSt, range	IS 1448 P:25	13.5 to 24	24 to 41
2	Viscosity Index, min	IS 1448 P:56	135	135
3	Flash Point, Cleveland (open) cup, °C, min	IS 1448 P:69	180	190
4	Copper Strip Corrosion, 121°C, 1 hr	IS 1448 P:15	3	3
5	Max. Temp. for Brookefield Viscosity of 1,50,000 CP, °C	ASTM D2983	-26	-12

Disclaimer: DC makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.